BASELAYR Y-SERIES EXPOSURE UNIT



Note: Not recommended to use pre-sensitized emulsions due to varying results in testing.



WARNING: Unit must be used in an area where others will not be exposed to the Open UV source. This Devices contain an intense UV light. DO NOT look directly into the UV light during operation. This can be harmful to the eyes even for brief periods of time. If viewing the UV light is necessary, Use UV filtered eye protection to avoid damage to your eyes. DO NOT remove bottom unless instructed by the manufacturer, doing so will put you at risk of electric shock.

Troubleshooting guide:

No power to unit:

1. Outlet: Check the power outlet and confirm it's working properly.

2. Power input: To check the power input, make sure the main power switch on the back is activated. Then make sure the power cord is securely connected.

3. Main fuse: Check main fuse in the back, between the power cord and power switch (replace the fuse if necessary).

Tips & recommendations

Exposure times: In order to best direct you to properly expose the screen we have compiled the following exposure advice. Screen exposure changes with variables of emulsion, stencil EOM (emulsion over mesh or thickness), mesh count, screen mesh color, film opacity, environment and art. These recommendations are guidelines, use them to establish a starting point for your own testing.

Halftone retention: While the advanced exposure calculator does provide a halftone scale to help you accurately calculate the percent of halftone dot retention in your design, we recommend the following:

- From the output options menu in your artwork program (Photoshop, Corel, or ai), select the option to print a density scale on your artwork.
- Utilize the Eye loupe included in your kit to view these with the most accuracy.

Halftone best practices for the FX:

- Mesh Count/4.5 = LPI maximum.
- LPI * 4.5 = mesh minimum.

BASELAYR 3-YEAR ELECTRICAL LIMITED WARRANTY

WHAT IS COVERED?

Baselayr warrants any Baselayr Branded electronic equipment to be free from defects in materials and workmanship for a period of 3 years from the original date of purchase. This Warranty covers all Baselayr Branded/Manufactured electrical equipment, excluding standard consumables, to be protected against defects, damages, or malfunctions under normal use during the Warranty period. If you discover a defect in a product covered by this warranty, we will replace the part or repair the product, using new or refurbished components, or if repair is not possible, replace the item, free of charge.

WHAT DOES THIS WARRANTY NOT COVER?

Shipping or travel associated with a replacement or repair. Any problem that is caused by abuse, misuse, or any "Act of God" circumstance (such as a flood) is not covered. Also, replacement of any standard consumables that have a natural wear and tear rate that will eventually result in that item needing to be replaced is not covered.

This Warranty is non-transferable and can only be used by the original purchaser.

If Standard Consumables are faulty or damaged upon receipt Baselayr will need to be notified within the first 48 hours.

ITEMS	COVERED	NOT COVERED
LIGHT TABLE	FRAME, POWER CHORD & PUSH BUTTON.	LIGHT BULBS & BALLASTS
LED UNITS	LED POWER SUPPLIES, AMBER LED POWER SUPPLY, TABLET CHARGER POWER SUPPLY, TABLET, RELAYS, POWER CHORD, FRAME & LID FRAME.	GLASS, FUSES, NEOPRENE, LED LIGHT, AMBER LEDS & SHOCKS.
DRYING CAB	ALL COMPONENTS COVERED.	
FAN BANKS	ALL ITEMS COVERED (FANS, BUTTONS, FRAME AND POWER SUPPLIES).	

Note: Logos, graphic elements and or photo images contained in this document may not be reproduced without the written consent of Baselayr.